

MCB211 Series

High Frequency, Lightweight Underwater Accelerometer, Top Exit
Molded Integral Cable, 10-32 Mounting, 10 mV/g, ±10%



VIBRATION ANALYSIS HARDWARE




Product Features

- ▶ Nylon Overmolded Accelerometer
- ▶ IP68 Rated
- ▶ High Frequency, 30 kHz Response

MCB211

CB127 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	MCB211	MCB221	Environmental		
Sensitivity (±10%)		10 mV/g	Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	30-1,800,000 CPM	0.5 Hz-30 kHz	Maximum Shock Protection		10,000 g, peak
Frequency Response (±10%)	60-900,000 CPM	1 Hz-15 kHz	Electromagnetic Sensitivity		CE Approved
Frequency Response (±5%)	120-600,000 CPM	2 Hz-10 kHz	Sealing		IP68 Integrally Molded Cable
Dynamic Range		± 500 g, peak	Physical		
Electrical			Sensing Element		PZT Ceramic
Settling Time		< 2 Seconds	Sensing Structure		Shear Mode
Voltage Source (IEPE)		18-30 VDC	Weight	0.35 oz	10 grams
Constant Current Excitation		2-10 mA	Mounting Base		316L Stainless Steel
Spectral Noise @ 10 Hz		100 µg/√Hz	Mounting		10-32 UNF
Spectral Noise @ 100 Hz		19 µg/√Hz	Cable Jacket Diameter		0.14 in (3.6 mm)
Spectral Noise @ 1000 Hz		5 µg/√Hz	Cable Jacket Material		Polyurethane
Output Impedance		< 100 ohm	Cable Conductor		26 AWG
Bias Output Voltage		10-14 VDC			Twisted Shielded Pair
Case Isolation		>10 ⁸ ohm	Resonant Frequency	2,640,000 CPM	44 kHz
			Mounting Hardware	10-32 Stud	M5 Stud
			Calibration Certificate		CA10

Typical Frequency Response



Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900