

# AC224 Series



VIBRATION ANALYSIS HARDWARE

Premium Miniature Industrial High G & High Frequency Mini-MIL Accelerometer, Side Exit 2 Pin Mini-MIL Connector, 10 mV/g, ±5%



## Product Features

Very High 500g Side Exit Accelerometer for High Amplitude Applications


Helps to Detect Gearbox Defects and Other High Frequency Faults

- ▶ 1,0 - 15000 Hz (60-900,000 CPM) Frequency Response
- ▶ 10 mV/g ±5% Sensitivity
- ▶ 32 kHz Resonant Frequency

### AC224-1D

2 Pin Mini Mil Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

### AC224-2D

CB110 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

### AC224-3D

CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC224	M/AC224	<b>Environmental</b>		
Sensitivity (±5%)	10 mV/g		Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	60-900,000 CPM	1,0-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	90-420,000 CPM	1,5-7000 Hz	Electromagnetic Sensitivity	CE	
Frequency Response (±5%)	180-180,000 CPM	3,0-3000 Hz	Sealing	Welded, Hermetic	
Dynamic Range	± 500 g, peak		Submersible Depth	200 ft.	60 m
<b>Electrical</b>			<b>Physical</b>		
Settling Time	<2 seconds		Sensing Element	PZT Ceramic	
Voltage Source (IEPE)	18-30 VDC		Sensing Structure	Shear Mode	
Constant Current Excitation	2-10 mA		Weight	2.1 oz	60 grams
Spectral Noise @ 10 Hz	100 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 100 Hz	19 µg/√Hz		Mounting	1/4-28	
Spectral Noise @ 1000 Hz	5 µg/√Hz		Connector (Non-Integral)	2 Pin mini-MIL	
Output Impedance	<100 ohm		Resonant Frequency	1,920,000 CPM	32000 Hz
Bias Output Voltage	10-14 VDC		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Case Isolation	>10 <sup>8</sup> ohm		Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate		CA10

## Typical Frequency Response



Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900