

AC244 Series

Premium Miniature Industrial Accelerometer, High Frequency, Side Exit 2 Pin Mini-MIL Connector, 100 mV/g, ±5%



VIBRATION ANALYSIS HARDWARE



Product Features

Premium mini mil, Low Profile Industrial Accelerometer


100 mV/g ± 5% Sensitivity

- ▶ 2 Pin Mini-MIL Connection or Integral Cable
- Note: Integral Cable Options are only for Permanent Monitoring Applications

AC244-1D

2 Pin Mini Mil Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common




Stock Product

AC244-2D

CB110 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC244-3D

CB206 Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire




Built To Order

AC244-6D

CB611 Heavy Duty Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC244	M/AC244	Environmental		
Sensitivity (±5%)	100 mV/g		Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	36-900,000 CPM	0.6-15000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response (±10%)	60-600,000 CPM	1.0-10000 Hz	Electromagnetic Sensitivity	CE	
Frequency Response (±5%)	120-420,000 CPM	2.0-7000 Hz	Sealing	Welded, Hermetic	
Dynamic Range	± 50 g, peak		Submersible Depth	200 ft.	60 m
Electrical			Physical		
Settling Time	<2.5 seconds		Sensing Element	PZT Ceramic	
Voltage Source (IEPE)	2-10 VDC		Sensing Structure	Shear Mode	
Constant Current Excitation	2-10 mA		Weight	2.1 oz	60 grams
Spectral Noise @ 10 Hz	30 µg/√Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 100 Hz	4 µg/√Hz		Mounting	1/4-28	
Spectral Noise @ 1000 Hz	2 µg/√Hz		Connector (Non-Integral)	2 Pin mini-MIL (J Series)	
Output Impedance	<100 ohm		Resonant Frequency	1,192,600 CPM	26000 Hz
Bias Output Voltage	7-14 VDC		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Case Isolation	>10 ⁸ ohm		Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
			Calibration Certificate	CA10	

Typical Frequency Response



Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900