

TA935 Series



VIBRATION ANALYSIS HARDWARE

Low Capacitance, Class I, Division 2 / Zone 2 Dual Output Sensor,
Acceleration and Temperature, Top Exit 3 Pin Connector, 100 mV/g,
10 mV/°C, ±10%




Regulatory Information

Ex nA IIC T3 Gc	Ui = 28 Vdc Ii = 100 mA
AEx nA IIC T3 Gc	Ci = 0µf Li = 51uH Pi = 100 mW
CL I Groups A, B, C, D	CSA 221421
CL II Groups E, F, G; CL III	Sira 15ATEX2152X
CL I, Zone 2	Ex nA IIC T3 Gc
Operating Temperature Code: T3	
Ambient Temperature Range = -40 to 121°C	

TA935-1A

3 Pin Connector

Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common
C	(+) Temperature Voltage




Stock Product

TA935-2C

CB191 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire




Built To Order

TA935-3C

CB218 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	TA935	M/TA935	Environmental		
Sensitivity (±10%)	100 mV/g		Temperature Range	-40 to 250°F	-40 to 121°C
Frequency Response (±3dB)	30-900,000 CPM	0.5-15000 Hz	Maximum Shock Protection		5,000 g, peak
Frequency Response (±10%)	60-360,000 CPM	1.0-6000 Hz	Electromagnetic Sensitivity		CE
Dynamic Range		± 80 g, peak	Sealing		Welded, Hermetic
Temperature Measurement Range	38 to 250°F	3 to 121°C	Physical		
Temperature Output		10 mV/°C	Sensing Element		PZT Ceramic
Electrical			Sensing Structure		Shear Mode
Settling Time		<2 seconds	Weight	3.2 oz	90 grams
Voltage Source (IEPE)		18-28 VDC	Case Material		316L Stainless Steel
Constant Current Excitation		2-10 mA	Mounting		1/4-28
Spectral Noise @ 10 Hz		30 µg/√Hz	Connector (Non-Integral)		3 Pin MIL-C-5015
Spectral Noise @ 100 Hz		19 µg/√Hz	Resonant Frequency		1,380,000 CPM
Spectral Noise @ 1000 Hz		15 µg/√Hz	Mounting Torque		2 to 5 ft. lbs.
Output Impedance		<100 ohm	Mounting Hardware		1/4-28 Stud
Bias Output Voltage		10-14 VDC	Calibration Certificate		CA10
Case Isolation		>10 ⁸ ohm			

Typical Frequency Response



Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900