

# DP1008

Proximity Probe, 25 mm Probe Tip Diameter, with 1 1/4-12 or M30x2 Case Thread




## Product Features

Measure shaft vibration and displacement on machinery with fluid film bearings


Durable PPS over-molded probe tips withstand harsh conditions when monitoring critical machinery such as turbines and compressors

- ▶ 25 mm probe tip diameter with 1 1/4-12 or M30x2 threaded body
- ▶ Probe tip and body sealed to prevent leaking through cable
- ▶ Upgraded to include SecureLock connector

**DP100801**  
Standard Mount



**DP100803**  
Standard Mount



Lengths AA, BB, and CC are configurable

## Specifications

Temperature Range	-49 to 340°F (-45 to 171°C)
Sensitivity	-20 mV/mil (-0.787 V/mm) (1 mil = 0.001")
Material	FEP Cable Jacket with 316L Stainless Steel Probe Body
Case Thread	1 1/4-12 or M30x2
Wrench Flats	1 1/8 in or 27 mm
Rating	IP68
Connector	SecureLock
Bending Radius	1.16 in (2.95 cm)

**Built to Order**

Lifetime Warranty on Materials & Workmanship  
[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900